








Tahoma[®]





























Tahoma V2 2.3



Connected Home (Tahoma Box)	
Intuitive	Convenient interface to centralize & control the equipment of the house, even remotely
Evolutive	Compatible with a wide range of equipment from Somfy and its partners
 Agenda	Manage your connected home to suit your lifestyle
 Smart	Automate devices depending on conditions (sensors, detectors, timer, etc.)
 Scenarios	Activating simultaneously several equipment by a single click. <i>(Only available on Premium offer)</i>

Installation	
1/ Connect Tahoma box to the Internet box/router (using the supplied RJ45 cable) and to the power supply (with the supplied cable)	
2/ Activate Tahoma on: www.somfy-connect.com	
3/ Start using Tahoma by setting-up your Connected home	
=> Use the Tahoma web interface or download the Tahoma mobile applications	



Compatibility	
Mobile applications	  iPhone from iOS 8.0  Android from Android 4.0.1
Web Browsers* <i>(*last version)</i>	     
Protocols	   Protocole Honeywell With Dongle  Green Smart, We see enocean With Dongle  Z-WAVE With Dongle
Partners	 atlantic  CIAT  Danfoss  Dimplex  Thermor  VELUX  De Dietrich  HITACHI Inspire the Next  Honeywell  HOPPE  KFV Ein Unternehmen der SEGENA GRUPPE  DolceVita  hue  Jauter

TaHoma[®]

Tahoma V2 2.3



Technical Specifications	
Element	TaHoma
Protocols/Frequency	Io-homecontrol – (868-870Mhz) RTS (433Mhz)
Range radio	200m free field 20m through 2 concrete walls
Dimensions (lxPxxh)	96 x 109 x 115 mm
Weight	≈ 235gr
Power	μUSB 5VDC / 1,75A Power supply 110/230V- 50/60 Hz (E/F/J Type compliant)
Consumption	0,1 A (nominal)
Connectors	1x Ethernet RJ45 1x Micro-USB (power supply) 1x USB port
Operating ambient temperature	+0°C to +50°C / IP 20
Color	White
Others	LED (Red/Green/Orange/White) “Reset” button
In the box	1x USB power adapter 1x RJ45 cable 1m 2x Quick start guides 1x Legal notice

Functional Specifications	
Max equipments (all protocols): 200*	
Equipments	Max
IO equipments	200
RTS equipments	50
RTD equipments	50
RTDS equipments	50
Ramses equipments	3 Evotouch
EnOcean equipments	128
OVP equipments	200
Caméras equipments	5
Zwave equipments	232
Scenario player equipments	20
HUE Bridge	1 (50 lamps)
De Dietrich	1 Gateway (1 Heating system)
Atlantic	200
Functions	Max
Scenario	40
Day	40
SMART	20
Others	Max
Condition in a SMART	2 or 6**
E-mail alerts	1 or 3**
SMS numbers alerts	1 or 3**
Push alerts	Unlimited

*More equipments is possible but not guaranteed.

**Only for TaHoma Premium offer.